

Technical characteristics

- Protection index

(considering a complete installation, including cover plate)

Penetration by solid bodies/liquid: IP20D

- Mechanical characteristics

Impact test: IK 04

- Material characteristics

Material:

Mechanism: Zamak

Key cover: ABS

Halogen free.

UV resistant.

Self-extinguishing: 650° C / 30 s

- Electrical characteristics

- Male TV connector Ø 9.52 mm to IEC 61169-2

- Female FM connector Ø 9.52 mm to IEC 61169-2

- SAT FM connector Ø 9.52 mm to IEC 61169-2

- "F" SAT screw-in connector Ø 9.4 mm

- Self-extinguishing: 650° C / 30 s

- Frequency bands: TV: 5 - 68 / 120 - 862 MHz

FM: 87.5 - 108 MHz

SAT: 950 - 2400 MHz

- Typical impedance: 75 Ω

- Feedback channel on TV connector

- Loss through shield: UHF > 65 dB

VHF > 75 dB

SAT > 55 dB




- Max. Ø of incoming cable on input: 7 mm

- Climatic characteristics

Storage temperature: - 10° C to + 70° C

Use temperature: - 5° C to + 35° C

Performance

Cat. No.	Zo				B1	FM	VHF	UHF	SAT IF	
	Ohm			22 / 0.6	40 - 68	87.5 - 108	120 - 470	470 - 862	950 - 2150	
	Ω		V/mA	KHz / V	MHz	MHz	MHz	MHz	MHz	
..5202D ..5202F	75		500 mA	1.5 dB						
..5202P14	75				14 dB					
..5202P10	75				10 dB					
..5214D	75	TV			1.5 dB					
		SAT	500 mA	1.5 dB					1.5 dB	
..5210M2D	75	TV			1.5 dB		1.5 dB			
		RD				1.5 dB				
		SAT	500 mA	1.5 dB					1.5 dB	

Standards and approvals

Compliance with standards CEI/EN 61169-1
CEI/EN 61169-2
CEI/EN 61169-24.

Refer to e.catalogue.

Cleaning

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Caution: Always test before using special cleaning products.